




Product Overview


The Downlight fixture, model DLJ15112-109 Series, is designed for recessed installation. The fixture can adjust the light direction by 45 degrees. It is used in conjunction with an LED MR16 GU5.3 bulb and operates with Central Battery Systems, at 12VDC. In case of a power outage, it provides emergency lighting for safety.

Dimensions (mm)

FRONT VIEW



SIDE VIEW



Technical Specifications	
Operating Temperature	10 to 50°C
Input Voltage	12VDC
LED Lamp Power	9W
Luminous Intensity	810 lm
Bulb Type	LED MR16
Base	GU5.3
Color Temperature	Warm White (3000K±250K) Daylight (6000K±250K)
Color Rendering Index	>80
Lamp Life Time	50,000 Hrs
Rated Beam Angle	50Deg
Degree of Protection	IP20
Dimension LxWxH	127 x 127 x 80 mm
Material	Diecasting aluminium
Weight	0.24 Kg
Hole cut	110 mm
Mounted	Recessed Ceiling

IsOn Import-Export Co., Ltd. | All rights reserved | LED Downlight Product Datasheet | Rev.141023 2915-2917 Ladprao Road, Klongjan, Bangkapi, Bangkok 10240 Thailand | www.sunnyemergencylight.com | intertrade@sunnyemergencylight.com