



Technical Specifications

Product Overview

The Remote Lamp of the RST Series (Double Lamp) is of the ceiling-mounted installation type. The lamp body is made of Stainless Steel Grade 304, which is corrosion-resistant and does not rust. It has an IP66 protection rating, making it suitable for installation in areas prone to dust and water spray. This helps protect the equipment inside the lamp from potential damage. The lamp can adjust the light direction in two ways, to the left and right, with an approximate range of 180 degrees, and it can also tilt up and down at an angle of about 45 degrees in practical installation. It operates in conjunction with LED MR16 GU5.3 bulbs and receives electrical power from the Central Battery Systems, which operate at 220VAC. In the event of a power outage, it provides emergency lighting for safety purposes.


Dimensions (mm)

· · · · · · · · · · · · · · · · · · ·	
Operating Temperature	0 to 60°C
Input Voltage	220 - 240VAC/ 50Hz
LED Lamp Power	12W / Bulb
Luminous Intensity	1,080 lm / Bulb
Bulb Type	LED MR16
Base	GU5.3
Color Temperature	Warm White (3000K±250K) Daylight (6000K±250K)
Color Rendering Index	>80
Lamp Life Time	50,000 Hrs
Rated Beam Angle	50Deg
Degree of Protection	IP66
Dimension LxWxH	245 x 95 x 150 mm
Material	Grade 304 stainless steel
Weight	1.01 Kg
Hole cut	-
Mounted	Surface Ceiling


Definition of the second secon

FRONT VIEW

SIDE VIEW



TOP VIEW



IsOn Import-Export Co., Ltd. | All rights reserved | Remote Lamp Product Datasheet | Rev.271023

2915-2917 Ladprao Road, Klongjan, Bangkapi, Bangkok 10240 Thailand | www.sunnyemergencylight.com | intertrade@sunnyemergencylight.com

The company reserves the final right for explanation on any of the information presented hereby.