LIGHT FOR LIFE

Model : RST 220-212(W)



The Remote Lamp of the RST Series (Double Lamp) is of the wall-mounted installation type. The lamp body is made of Stainless Steel Grade 304, which is corrosion-resistant and does not rust. It has an IP66 protection rating, making it suitable for installation in areas prone to dust and water spray. This helps protect the equipment inside the lamp from potential damage. The lamp can adjust the light direction in two ways, to the left and right, with an approximate range of 180 degrees, and it can also tilt up and down at an angle of about 45 degrees in practical installation. It operates in conjunction with LED MR16 GU5.3 bulbs and receives electrical power from the Central Battery Systems, which operate at 220VAC. In the event of a power outage, it provides emergency lighting for safety purposes.

| Operating Temperature | 0 to 60°C | H 180 | |
|-----------------------|--|------------|------------|
| Input Voltage | 220 - 240VAC/ 50Hz | FRONT VIEW | |
| LED Lamp Power | 12W / Bulb | | |
| Luminous Intensity | 1,080 lm / Bulb | | L 210 |
| Bulb Type | LED MR16 | | · |
| Base | GU5.3 | | |
| Color Temperature | Warm White (3000K ± 250K) Daylight (6000K ± 250K) | SIDE VIEW | 1 100 |
| Color Rendering Index | >80 | | |
| Lamp Life Time | 50,000 Hrs | | 71 W 95 |
| Rated Beam Angle | 50Deg | | |
| Degree of Protection | IP66 | | |
| Dimension LxWxH | 210 x 95 x 180 mm | 0 | |
| Material | Grade 304 stainless steel | BACK VIEW | |
| Weight | 1.01 Kg | | |
| Hole cut | _ | | 175 |
| Mounted | Surface Wall | | L 210 |

IsOn Import-Export Co., Ltd. | All rights reserved | Remote Lamp Product Datasheet | Rev.271023

2915-2917 Ladprao Road, Klongjan, Bangkapi, Bangkok 10240 Thailand | www.sunnyemergencylight.com | intertrade@sunnyemergencylight.com

I he company reserves the final right for explanation on any of the information presented hereby.